

B&P File No. 13533-1

BERESKIN & PARR

UNITED STATES

Title: Arm Protection Device

Inventor(s): Mark Christopher McKenzie

Title: Arm Protection Device

FIELD OF THE INVENTION

[0001] The present invention relates to devices which protect parts of
5 the body from harm, and in particular, to devices for protecting an arm from
fire, punctures, and infectious agents.

BACKGROUND OF THE INVENTION

[0002] Persons involved in fire fighting, law enforcement, and
emergency medical services require protection from a variety of hazards.
10 These hazards include infectious agents, fire, chemicals, and stab or puncture
wounds. However, current uniforms and attire generally provide little or no
protection to the arms, particularly when they comprise a short-sleeved shirt.

[0003] Prior art devices provide some arm protection. For example,
U.S. Patent Number 5,628,062 (Tseng) discloses an arm and hand protective
15 sleeve that helps prevent automotive drivers from contracting skin damage or
skin diseases from ultraviolet solar radiation while driving. U.S. Patent
Number 5,642,525 (Ketola) discloses a bandage for protecting an elbow
without providing any sliding contact between the bandage and the elbow.
U.S. Patent 6,464,669 (Wilke) discloses a protective sheeth that may be slid
20 over a patient's arm or leg for holding a peripherally inserted central catheter
in place.

[0004] These prior art devices have a number of disadvantages. None
of the devices appears to provide substantial protection against fire,
punctures, or infectious agents. The device disclosed by Ketola does not
25 extend fully from the upper arm to the lower arm. All of these devices must be
removed from the arm for storage. None of these devices is designed to
securely fasten to the clothes of the wearer, which may make their use
inconvenient and reduce the speed with which they can be deployed. There
is accordingly a need for an arm protection device which overcomes the
30 disadvantages of the prior art.

SUMMARY OF THE INVENTION

[0005] The present invention is directed to a device for protecting the arm of a user wearing a shirt. The device comprises a sleeve made of a protective fabric and a tubular fabric pouch. The sleeve can be extended from
5 a retracted position to an extended position. The sleeve is shaped and sized to envelop a user's lower arm when the sleeve is in its extended position. The lower end of the sleeve has a hand opening sized to allow the user's hand to extend therethrough.

[0006] The pouch is sized to extend around the user's upper arm, and
10 shaped to provide a circumferentially extending storage cavity for storing the protective sleeve. The pouch includes closure means for releasably closing the storage cavity when the sleeve is stored inside in the retracted position, and attachment means for attaching the pouch to an upper arm portion of the user's shirt. The upper end of the sleeve is affixed to an inner portion of the
15 pouch.

[0007] The tubular fabric pouch may consist of an inner sleeve portion and an outer sleeve portion. The outer sleeve portion may be folded over the inner sleeve portion to form a folded position, which defines the storage cavity. The outer sleeve portion may be attached to the inner sleeve portion
20 along a circumferential line of attachment. The inner sleeve portion and outer sleeve portion of the pouch have inside surfaces facing each other in the folded position. The outer sleeve portion may be folded inside out to form an unfolded position exposing the inside surfaces of the outer sleeve portion and the inner sleeve portion to facilitate replacing the sleeve in the retracted
25 position after deployment.

[0008] The cavity closure means may comprise a plurality of circumferentially spaced pairs of snaps located adjacent the lower circumferential edges of the sleeve portions of the pouch. The lower end of the protective sleeve may comprise a cuff having adjusting means for
30 adjusting the size of the hand opening.

[0009] The sleeve may comprise a fastening means to adjustably and securely fasten the lower end of the sleeve around the user's wrist. The sleeve may have a tapered lower end to better fit the lower arm. The sleeve may be provided with a slit in the lower arm portion with a slit closure means
5 for releasably closing the slit.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The invention will now be described, by way of example only, with reference to the following drawings, in which:

[0011] Figure 1 is a perspective view of a preferred embodiment of an
10 arm protection device made in accordance with the present invention, shown attached to a user's garment;

[0012] Figure 2 is a top plan view of the subject arm protection device, showing the protective sleeve in the fully extended position and the outer sleeve portion of the tubular pouch folded inside out;

15 [0013] Figure 3 is a perspective view of the subject arm protection device, showing the protective sleeve in the retracted position inside the tubular pouch;

[0014] Figure 4 is a perspective view of the arm protection device of the present invention, showing the protective sleeve in the process of being
20 extended from the tubular pouch;

[0015] Figure 5 is a perspective view of the subject arm protection device, shown deployed on a user's arm, with the protective sleeve in the extended position, before the sleeve is fastened around the user's wrist; and

[0016] Figure 6 is a perspective view of the subject arm protection
25 device, shown in a fully deployed position, with the protective sleeve fastened around the user's wrist.

DETAILED DESCRIPTION OF THE INVENTION

[0017] Referring to Figure 1, illustrated therein is a preferred embodiment of an arm protection device 10 made in accordance with the
30 subject invention, shown deployed on a user's short sleeve shirt 16. Arm

protection device 10 comprises a tubular fabric pouch 14 and a protective sleeve 12, shown in dotted lines, stored within pouch 14. Tubular pouch 14 is sized to extend around upper arm portion 11 of shirt 16, and shaped to form a circumferentially extending storage cavity 19 for storing protective sleeve 12 in a retracted position. Tubular pouch 14 includes closure means 20, comprising snaps in this embodiment, for closing storage cavity 19. Tubular pouch 14 includes shirt attachment means 18 for securely and releasably attaching pouch 14 to upper arm portion 11. Shirt attachment means 18 is preferably a zipper comprising an upper row of zipper teeth 18a sewn to upper arm portion 11, a lower row of zipper teeth 18b sewn to the top of pouch 14, and zipper slide 18C which engages teeth 18a, 18b to open and close the zipper.

[0018] Referring now to Figure 2, illustrated therein is arm protection device 10 with tubular pouch 14 folded inside out and protective sleeve 12 in a fully extended position. Tubular pouch 14 comprises an inner sleeve portion 22 and an outer sleeve portion 24. Inner sleeve portion 22 and outer sleeve portion 24 have upper circumferential edges 26a, 26b and lower circumferential edges 30a, 30b, respectively. Upper circumferential edges 26a, 26b are attached, preferably sewn, to each other along a circumferential line of attachment 28. Thus, when the outer sleeve portion 24 is folded over inner sleeve portion 22, sleeve portions 22, 24 form the walls of storage cavity 19 (shown in Figure 1) in which protective sleeve 12 is stored in the retracted position when not in use. Lower circumferential edges 30a, 30b of inner sleeve portion 22 and outer sleeve portion 24 are not attached to each other and create an opening from which the sleeve 12 may be withdrawn for deployment.

[0019] Inner sleeve portion 22 of pouch 14 comprises an inside surface 32, and outer sleeve portion 24 of pouch 14 comprises an inside surface 34. Upper end 40 of protective sleeve 12 is attached to inside surface 32 of inner sleeve portion 22 along a circumferentially extending line of attachment 29 spaced from lower circumferential edge 30a of inner sleeve portion 22. Male

5 snap portions 20a of closure means 20 are located between circumferential line of attachment 29 and lower circumferential edge 30a of inner sleeve portion 22, and female snap portions 20b of closure means 20 are located along lower circumferential edge 30b of outer sleeve portion 24. When outer sleeve portion 24 is folded over inner sleeve portion 22, snap portions 20a, 20b may be fastened together to releasably close pouch 14.

[0020] As further illustrated in Figure 2, protective sleeve 12 comprises an upper main portion 64 of substantially constant diameter and a lower tapered portion 66 having a progressively decreasing diameter to better fit the user's lower arm. Tapered lower portion 66 comprises a cuff portion 42 having a hand opening 44 sized to allow a user's hand to extend through, and adjusting means 46 for adjusting the size of the hand opening to fit a user's wrist.

[0021] Referring now to Figure 3, tubular pouch 14 is shown in its folded over position, with protective sleeve 12 stored in its retracted position in cavity 19. Snaps 20a, 20b are shown unsnapped, exposing inside surfaces 32, 34, and allowing protective sleeve 12 to be removed from pouch 14.

[0022] Referring now to Figure 4, arm protection device 10 is shown with protective sleeve 12 in the process of being removed from tubular pouch 14. The user may extend sleeve 12 by pulling sleeve 12 downward in the direction of the arrow.

[0023] Referring now to Figure 5, arm protection device 10 is shown deployed on a user's arm, with the protective sleeve 12 in the extended position. Protective sleeve 12 has been pulled downward, thus exposing main portion 64 of sleeve 12 and the tapered portion 66 of sleeve 12. Tapered portion 66 is provided with a longitudinally extending slit 70 which splits cuff portion 42 in two, and slit closure means 72, comprising a zipper in the preferred embodiment, for releasably closing slit 70. Adjusting means 46 of cuff portion 42 allows the user to adjust the size of hand opening 44 to securely fit cuff portion 42 around user's wrist 50 once the user's hand 48 has been extended through sleeve 12. Adjusting means 46 is preferably a Velcro

(trade mark) hook and loop fastener, comprising a first strip 46a extending from cuff corner 52 and a second strip 46b extending around the circumference of cuff portion 42. Velcro strip 46b has loops shaped to be releasably secured to hooks of Velcro strip 46a.

5 **[0024]** Referring now to Figure 6, arm protection device 10 is shown fully deployed with protective sleeve 12 in the fully extended position. Adjusting means 46 is shown closed around user's wrist 50, with first Velcro strip 46a removably secured to second Velcro strip 46b.

10 **[0025]** In the preferred embodiment, the pouch and sleeve are constructed from a pre-selected protective material, comprising, in the preferred embodiment, Nitrile coated nylon with Kevlar netting. The netting may be structured similarly to the netting found in duct tape.

15 **[0026]** The present invention is deployed in the following manner. As shown in Figure 1, tubular pouch 14 of arm protection device 10 is attached to upper arm 11 of the user's short-sleeve shirt 16 by attachment means 18. Protective sleeve 12 is stored in the retracted position within the tubular pouch 14 and is maintained in that position by closure means 20. When the user wishes to deploy sleeve 12, the user unfastens snaps 20a, 20b and removes sleeve 12 by pulling it downward as shown in Figure 4. As illustrated in 20 Figure 5, once the sleeve is extended, the user closes slit 70 by operating closure means 72. As further shown in Figures 2, 5, and 6, the user then securely fastens cuff portion 42 around wrist 50 by adjustably fastening Velcro strips 46a, 46b.

25 **[0027]** To replace protective sleeve 12 in the retracted position in tubular pouch 14 after use, the user first unfastens Velcro strips 46a, 46b. The user then unzips closure means 72 to open slit 70. Protective sleeve 12 may then be bunched up and inserted into cavity 19 of tubular pouch 14. This action exposes male snaps 20a on inner sleeve portion 22, which may then be attached to the female snaps 20b on outer sleeve portion 24, thus closing 30 tubular pouch 14.

[0028] Referring again to Figure 2, to facilitate replacing protective sleeve 12 in the retracted position, the user may optionally fold outer sleeve portion 24 of tubular pouch 14 upwards and inside out as shown in Figure 2, before protective sleeve 12 is placed in pouch 14. This allows the user to
5 bunch up protective sleeve 12 into the retracted position without being encumbered by the outer sleeve portion 24 of pouch 14. After protective sleeve 12 has been placed in the retracted position, the user folds outer sleeve portion 24 of tubular pouch 14 downwards and closes cavity 19 by fastening snaps 20a of inside sleeve portion 22 to snaps 20b of outside
10 sleeve portion 24.

[0029] While the preferred embodiment of the tubular pouch consists of two sleeve portions sewn together, the tubular pouch could comprise a single sleeve having a fold line, which could be folded over to form the storage cavity for the protective sleeve. While the preferred means for attaching the pouch
15 to a user's shirt is a zipper, the pouch could be permanently attached to the shirt, or the pouch could be releasably attached by alternative fasteners, such as Velcro strips or snaps. Similarly, the snaps and Velcro strips and other zipper of the preferred embodiment could be interchanged or replaced by alternative fastening means. In addition, the pouch and protective sleeve
20 could be constructed of alternative protective means, including reflective materials which would allow the user to be more visible for activities such as directing traffic.

[0030] It should therefore be apparent to one skilled in the art that various modifications can be made to the preferred embodiment disclosed
25 herein, without departure from the invention, the scope of which is defined in the appended claims.